1   A LIGHTING FIXTURE

2

3   CROSS-REFERENCE TO RELATED APPLICATION

4   This application claims the benefit, under 35 U.S.C. §119(e), of U.S.

5   Provisional Application No. 60/201,489; filed May 3, 2000.

6

7   FEDERALLY-SPONSORED RESEARCH OR DEVELOPMENT

8   Not Applicable

9

10   BACKGROUND OF THE INVENTION

11   The present invention relates to a lighting fixture for projecting a beam

12   of light and for use for spot lighting in connection with theater stages, cinema

13   and television studios and the like, the fixture comprising:

14   a light source arranged at one end of a housing having a light beam exit

15   aperture at the opposite end thereof, the light source and aperture being

16   arranged generally concentric with a longitudinal or optical axis of the

17   lighting fixture,

18   light beam influencing means at least comprising one or more,

19   preferably four, beam-shaping blades and preferably also comprising other

20   light influencing means such as one or more lenses and/or an iris and/or a

21   pattern or gobo, for influencing a light beam emitted by the light source and

22   being arranged along the path of the light beam along said longitudinal axis

23   through the housing from the light source to the aperture, and

24   adjustment means for adjusting the position of at least said one or more

25   beam-shaping blades and preferably of all said influencing means relative to

26   said longitudinal axis.

27   *The purpose of a lighting fixture as defined above is to produce a well-

28   defined light beam or light cone with a geometry, angle of conicity and focal

29   point that may be altered manually or by remote control.

1   A lighting fixture will normally comprise a light source, a reflector, a
2   beam-shaping gate with beam-shaping blades, a pattern or gobo, an iris, a
3   focusing lens, a zoom lens and a color filter as well as a suspension structure
4   allowing the lighting fixture to be pivoted vertically and horizontally.

5   The visible part of the light emitted by the light source is collected by
6   the reflector and is sent towards the iris, the gobo and the beam-shaping gate
7   as a parallel light beam. The infrared part of the radiation from the light
8   source passes through the dichroic coating of the reflector and impinges on
9   the inner surface of the housing surrounding the light source, the heat being
10 transported to the outer surface of the housing having cooling ribs for emitting
11 the heat to the surrounding atmosphere.

12   It is often necessary to be able to determine the geometry of the light
13 beam, and this is achieved by means of the zoom lens varying the angle of
14 conicity of the light cone and by shaping or cutting off the periphery of the
15 light beam by means of the beam-shaping gate with beam-shaping blades so
16 as to obtain geometrical figures such as squares, triangles, trapezoids etc. The
17 lenses project the light out through the aperture of the housing opposite the
18 light source and through the color filter at the front end of the lighting fixture.
19 It is important that the different elements influencing the shape and other
20 characteristics of the light beam function as precisely as possible even when
21 being influenced by the heat radiated from the light source and not removed
22 by means of the dichroic reflector. This entails that the location and the
23 configuration of the adjustment means for the beam-shaping blades, the gobo
24 and iris are such that any bending caused by the heat influence from the light
25 beam be kept at a minimum.

26   Lighting fixtures of this type are often arranged in places where it is
27 difficult to access them manually and it is therefore of great importance that
28 the adjustment means for adjusting the above-mentioned beam influencing
29 means be as easily accessed and as flexible as possible when manual operation

1 of the adjustment means is required.

2 U.S. Patent No. 5,345,371 discloses a lighting fixture of the type in

3 reference where the four beam-shaping blades or shutters are slidingly

4 insertable in slots from outside, the shutters being radially adjustable by

5 gripping a holder for each shutter and sliding the shutter in or relative to the

6 optical axis. The shutters may also be tilted manually to a certain extent.

7 However, a further tilting possibility is achieved by allowing the portion of

8 the fixture containing the shutters to be rotated as a unit around the axis. This

9 is a complicated solution and needs manual access to all holders of the

10 shutters as well as manipulation of the rotation means for rotating part of the

11 fixture. Motorization for remote control of this design will be very

12 complicated and costly.

13 U.S. Patent No. 4,890,208 discloses a lighting fixture of the type in

14 reference where four shutters are arranged for motorized displacement radially

15 toward the optical axis and motorized tilting by means of rack and pinion

16 mechanisms. This solution is complicated and has only limited tilting

17 capability, i.e. displacement capability circumferentially around the axis.

18 Furthermore this solution is not well suited for manual operation.

19

20 SUMMARY OF THE INVENTION

21 It is an object of the invention to provide a lighting fixture of the type

22 indicated, wherein access for manual operation is convenient and not

23 dependent on the orientation of the lighting fixture, wherein motorization for

24 remote control may be established in a simple and reliable manner and

25 wherein the range of displacement circumferentially around the optical axis is

26 as great as possible.

27 According to the invention this object is achieved by at least the

28 adjustment means corresponding to said one or more beam-shaping blades

29 and preferably all the adjustment means are arranged for rotation around said

1 longitudinal axis and are connected to a respective influencing means such

2 that rotation of the adjustment means around said longitudinal axis adjusts the

3 position of the respective influencing means relative to said longitudinal axis.

4   Hereby the adjustment means may be accessed from practically any

5 angle, and no limit to the adjustment possibilities in circumferential direction

6 is inherent.

7   In the currently preferred embodiment the adjustment means comprise

8 an annular body arranged with the axis thereof substantially coinciding with

9 said longitudinal axis. This is a particularly simple and effective embodiment.

10   In the currently preferred embodiment of the invention the annular

11 body comprises an outer rim configured for being engaged for applying

12 rotational force thereto, the surface of said outer rim being provided with

13 friction enhancing means such as roughening means, rubber surfacing,

14 projections or teeth. Hereby manual and remote operation of the adjustment

15 means is particularly simple and efficient.

16   Advantageously, the fixture further comprises one or more electrical

17 motors connected to a respective drive wheel engaging said outer rim of a

18 respective annular body for applying a rotational force thereto, and preferably

19 the drive wheel is a gear having teeth, and the respective outer rim engaged by

20 a respective gear is provided with teeth for meshing with the teeth of said gear

21 when said gear rotates.

22   For use in remote control of the lighting fixture with pre-determined

23 positions of the light influencing means, it is advantageous that the annular

24 body be provided with a position indicating means for indicating the angular

25 position of the annular body relative to said longitudinal axis. Hereby a

26 reference point for the remote control operation is available, thereby

27 eliminating errors and inaccuracies.

28   Advantageously, the position indicating means comprises an element

29 that may be remotely sensed such as a magnet or a gap, and the fixture further

1 comprises remote sensing means for sensing the angular position of said

2 element relative to said longitudinal axis.

3   So as to obtain the greatest flexibility of adjustment and the greatest

4 range of adjustment, the adjustment means for each of the one or more beam-

5 shaping blades comprises radial adjustment means for adjusting the position

6 of the blade radially relative to said axis, and circumferential adjustment

7 means for adjusting the position of said blade circumferentially around said

8 axis.

9   A particularly simple and efficient as well as accurate embodiment of

10 the light fixture according to the invention is provided by the adjustment

11 means for each of the one or more beam-shaping blades comprising two

12 adjacent co-centrical annular bodies or rings each connected to one point of

13 the blade such that relative rotation of the two rings alters the radial position

14 of the blade.

15   In the currently preferred embodiment, the rings comprise guiding

16 tracks recessed into the lateral surface of each ring facing the other ring, and

17 each blade comprises a body extending generally transversely to said axis and

18 two arms extending generally parallel to said axis, the arms each being

19 provided with sliding connecting means for connecting the respective arm to

20 each of the rings and being adapted for being slidingly received in a guiding

21 track in each of said rings.

22

23   BRIEF DESCRIPTION OF THE DRAWINGS

24   In the following description, preferred embodiments of a lighting

25 fixture according to the invention will be described in detail, solely by way of

26 example, with reference to the accompanying drawings, where:

27   Fig. 1 is an isometric elevational view of a lighting fixture according to

28 the invention for manual operation;

29   Fig. 2 is a partially cut-away view of the lighting fixture in Fig. 1

1 illustrating the internal configuration of the lighting fixture;

2   Fig. 3 is a schematic cross-sectional view of the lighting fixture of Figs

3 1 and 2, the cross-section being taken along a vertical plane containing the

4 longitudinal or optical axis of the lighting fixture;

5   Fig. 4 is an enlarged scale view of the left-hand part of Fig. 3;

6   Fig. 5 is an isometric elevational view of the bottom half of the frame

7 of the lighting fixture of Figs. 1 and 2;

8   Fig. 6 is an exploded view of the beam-shaping blades and adjustment

9 rings of the fixture in Figs. 1 and 2;

10   Fig. 7 is an axial end view of the blades and rings shown in Fig. 6 in

11 nested assembled condition;

12   Figs. 8 and 9 are schematic axial end views corresponding to Fig. 7

13 illustrating the adjustment of the beam-shaping blades of Figs. 6-7;

14   Fig. 10 is an illustration of the constructive principles of the guiding

15 tracks in the adjustment rings for the beam-shaping blades;

16   Fig. 11 schematically illustrates an alternative embodiment of the

17 beam-shaping blades and the adjustment mechanisms therefor;

18   Fig. 12 shows an isometric partly exploded view in larger scale of the

19 position adjustment mechanism for the lenses shown in Fig. 2; and

20   Fig. 13 shows an enlarged view of a detail of the construction shown in

21 Fig. 12.

22

23   DETAILED DESCRIPTION OF THE INVENTION

24   Referring now to Figs 1-5, a lighting fixture 1 according to the

25 invention is suspended in a suspension fitting 2 having an aperture 3 for

26 fixing the fitting 2 pivotably to a support structure (not shown) in a theater, a

27 television studio or the like. The fitting 2 is pivotably attached to the body of

28 the lighting fixture 1 at 4, the attachment point being adjustable by sliding the

29 pivot attachment point 4 in a slit 5 in a frame 6 so as to compensate for change

1 of balance because of insertion or removal of different elements in the

2 lighting fixture 1.

3   The lighting fixture 1 may thus be manually pivoted around two

4 mutually substantially orthogonal axes allowing the direction of a light beam

5 emitted by the fixture to be any desired direction.

6   If it is desired to be able to remotely control the direction of the beam,

7 the pivoting action may be achieved by means of remotely controlled

8 electrical motors in many different ways that will be obvious to those skilled

9 in the art.

10   The frame 6 is generally U-shaped having two arms supporting the

11 body of the lighting fixture 1 between said arms. A series of toothed rims 7-18

12 are arranged for rotation around a longitudinal or optical axis 19 (see Fig. 3).

13 The teeth of the toothed rims are configured such that the teeth of a pinion of

14 a drive unit may engage and mesh therewith if the light beam influencing

15 facilities of the lighting fixture operated by rotation of the bodies 7-18 are to

16 be motorized for remote control.

17   In the manually operated embodiment shown in Figs 1-4, the teeth of

18 the toothed rims serve as a roughening element of the surface of the rim of

19 each of the annular bodies 7-18 such that good frictional engagement between

20 the fingers of a hand and the toothed rims or annular bodies 7-18 may be

21 achieved for rotating the annular bodies 7-18 manually.

22   Such roughening of the rim surface may be achieved in many other

23 ways such as scoring of the surface or coating with rubber or provision of

24 small projections etc.

25   In such case and if motorization of the rotation of the bodies 7-18 is

26 desired, then a frictional surface engagement of for instance the surface of a

27 rubber coated drive wheel driven by an electrical motor with the roughened

28 rim surface may be provided for instead of the meshing of the teeth of a

29 pinion with teeth of the rim of the annular body.

1   A light source or lamp 20 emits a light beam composed of individual

2   light beams such as illustrated at 20a, the visual portion thereof being

3   reflected by a dichroic reflector 21 through a focusing lens 22 and a zoom lens

4   23 and out of the lighting fixture through an aperture 24 in the housing 25 of

5   the fixture 1, the light beam 20a traveling through a color filter (not shown)

6   arranged in four color filter holders 26 that may be pivoted around pivots 27

7   so as to allow a color filter to be inserted and removed in the holders 26 in any

8   of four directions determined by the four holders 26. Hereby the color filter

9   may be inserted and removed from the best angle for manual access for a

10   given orientation of the housing 25. The entire light beam projected by the

11   lighting fixture is of course composed of a plurality of light beams analogous

12   to individual light beam 20a.

13   The infra red portion of the light beam 20a is transmitted through the

14   dichroic reflector 21 to cooling ribs 22 in a manner well known in the art so as

15   to reduce the heat distortion of light beam influencing elements, as described

16   below, that are arranged along the path of the light beam from the light source

17   20 to the exit aperture 24.

18   These light beam influencing elements comprise an iris 28 connected

19   to the annular body 7, a pattern or gobo 29 connected to the annular body 8,

20   four beam-shaping blades 30, 31, 32 and 33 connected to the pairs of annular

21   bodies, 9 -10, 11-12, 13 –14 and 15 -16, respectively, the focusing lens 22

22   connected to the annular body 17, and the zoom lens 23 connected to the

23   annular body 18.

24   The annular bodies or rings 7-18 are connected in different manners to

25   the respective light beam influencing elements 22, 23 and 28-33 so that the

26   position of these elements may be altered relative to the axis 19, and thus the

27   light beam, by rotating the rings around said axis. The individual connections

28   between the individual rings and the respective elements will be described

29   more in detail below.

1   The feature of being able to alter the position of the light beam

2   influencing elements, and particularly of the light beam shaping blades 30-33,

3   by means of rotating the corresponding rings allows the position alteration to

4   be carried out manually from a convenient angle of approach for a given

5   orientation of the housing 25. As the rim surface of each of the rings 7-18 may

6   be engaged manually at most of the extent of the circumference thereof, the

7   manual adjustment of the position of a respective light beam influencing

8   element may be performed from the most convenient angle of approach to the

9   housing 25. Furthermore, the manual adjustment may be carried out with one

10   hand which is important, as the fixture is often located such that access with

11   both hands is difficult and perhaps impossible.

12   Hereby the lighting fixture according to the invention does not have the

13   disadvantages of known lighting fixtures where the adjustment means for

14   adjusting the position of a light beam shaping blade may be very

15   inconveniently located relative to the position of the person operating the

16   lighting fixture so that the person for instance has to reach around the lighting

17   fixture housing to access the adjustment means thereby risking being burned

18   on the hot housing surface and rendering rapid and precise position

19   adjustment difficult and perhaps impossible.

20   This advantage can also be obtained by rotational means other than

21   rings with a rim surface for being engaged manually or mechanically.

22   Elements having a plurality of radially extending spokes spaced

23   circumferentially for being engaged at the ends thereof by fingers of a hand or

24   a motorized driving means may also be used. A circumferentially disposed

25   endless belt arranged for substantially circular movement around the

26   longitudinal axis may also be utilized instead of the illustrated rings. All

27   means allowing access along a major part of the circumference of the housing

28   and rotational frictional engagement by fingers or a motorized drive unit may

1   be used to allow such convenient access to the adjustment means for altering

2   the position of the beam influencing elements.

3   The feature of altering the position of the light influencing elements by

4   rotational means also entails simple and reliable establishment of a certain

5   adjustment setting of a respective influencing means such that pre-

6   programmed settings may be set up for certain lighting requirements knowing

7   that it will be simple, quick and reliable to achieve such settings either

8   manually or remotely under difficult conditions, for instance during the course

9   of a theater show where adjustments in the dark are necessary.

10   A further advantage is obtained by the shown structure according to the

11   invention in that the construction is such that no light is emitted from the

12   interior of the fixture except through the aperture 24, and all adjustments of

13   the light beam influencing elements may be carried out without creating a

14   light emission slit or aperture. Hereby, the disadvantage of all known lighting

15   fixtures that light "leaks" therefrom is eliminated which is of great value,

16   particularly for theater use.

17   Referring again to Figs. 1- 5, the frame 6 is constituted by two identical

18   halves 6a and 6b abutting each other at 6c. The rings or annular bodies 7-18

19   are rotatably and slidingly supported in annular grooves 34 in annular support

20   rings 35 by means of annular projections or ridges 36 slidingly received in the

21   annular grooves 34. The support rings 35 are each constituted by half a ring

22   fixedly attached to or made in one piece with one half of the frame 6, for

23   instance 6a (see Fig. 1). In other words each of the frame halves 6a and 6b is

24   fixedly attached to or integral with a series of half rings 35 as shown in Fig.

25   5, where the bottom half 6b of the frame 6 is shown with the corresponding ,

26   half rings 35.

27   When assembling the lighting fixture 1, the adjustment rings 7-18 with

28   corresponding beam influencing elements 22, 23 and 28-33 are arranged in

29   the bottom half 6b of the frame with corresponding half rings 35 such that the

1   ridge 36 of each adjustment ring is received in the corresponding groove 34 of

2   the respective half ring 35 of the bottom frame half 6b. Thereafter the top half

3   6a of the frame 6 with corresponding half rings 35 is placed abutting the

4   bottom half 6b at 6c such that the ridge 36 of each adjustment ring is received

5   in the corresponding groove 34 of the respective half ring 35 of the top frame

6   half 6a. The adjustment rings 7-18 will thus be slidingly and rotationally

7   supported along the entire circumference thereof by the corresponding rings

8   35.

9   Each of the adjustment rings or annular bodies 7-18 may then be

10 rotated manually or by means of suitable mechanical means by applying a

11 tangential force to the rim of the respective adjustment ring whereby the ridge

12 36 thereof slides in the respective annular groove 34 of the respective support

13 ring 35. The material of the ridges 36 and the grooves 34 are chosen such that

14 frictional sliding resistance is kept at a minimum. The support rings 35 may

15 be made of cast aluminum, and the adjustment rings may be made of glass-

16 fiber reinforced plastic. The ridges 36 are made of a low frictional material

17 such as PTFE (marketed, for example, under the trademark "TEFLON"), a

18 ring of said material being embedded in the lateral surface of the

19 corresponding adjustment ring. Hereby the frictional sliding resistance

20 between the low friction material and the cast aluminum will be low, and the

21 adjustment rings may consequently be rotated by applying a relatively small

22 tangential force to the rim thereof.

23   Each of the adjustment ring pairs 9/10, 11/12, 13/14 and 15/16 carries

24 a respective light beam shaping blade 33, 32, 31 and 30, respectively, by

25 means of pairs of arms 33a,b, 32a,b, 31a,b and 30a,b, respectively, held by the

26 adjustment ring pairs in a manner described more in detail below. So that the

27 two rings of each ring pair can rotate relative to one another, a low friction

28 material ring 37 is arranged between each pair of adjustment rings as

29 illustrated in Figs. 4 and 6.

1   Referring now to Figs. 4 and 6-9, the arrangement of the four light

2   beam shaping blades 30-33 will now be explained more in detail.

3   The blades 30-33 are nested as illustrated in Figs. 4, 6 and 7, each

4   blade 30-33 being carried by a pair of opposed arms, 30a-33a and 30b-33b,

5   respectively. It is important that the blades 30-33 are located as axially close

6   to each other as possible so as to achieve a sharp cut-off boundary of the light

7   beam all around the circumference thereof which only can be achieved if the

8   blades are arranged such that there is no substantial distance between them in

9   the axial direction of the housing. This is particularly well illustrated in Figs. 3

10   and 4 where it is evident that the spacing of the blades in the direction of the

11   axis 19 is slight.

12   The arrangement shown also has the advantage that the axial distance

13   between the beam-shaping blades 30-33 and the iris 28 as well as the gobo or

14   pattern 29 is small so that a good sharpness or quality of the influence of the

15   blades, the iris and the gobo on the light beam may be obtained

16   simultaneously because of the small axial distance covered by all said

17   elements.

18   The blades 30-33 are shaped as shown in Figs. 6-8 having a generally

19   elliptical planar body 38 with an aperture 39 having a periphery comprising a

20   curved portion 40 and linear portions 41, 42 and 43, said periphery serving as

21   the beam cut-off edge of the blade body 38. This is illustrated in Fig. 7 where

22   the peripheries of the apertures 39 of the four bodies 38 of the blades 30-33

23   define the periphery of the beam shaping aperture 44. A multitude of

24   different shapes of the aperture 44 may be achieved by a combination of a

25   rotation of the different blades 30-33 around the axis 19 with a displacement

26   of said blades 30-33 radially relative to said axis 19.

27   The radial displacement of the individual blades 30-33 is illustrated in

28   Figs. 8-9 where the periphery portion 42 of blade 33 is shown in Fig. 8 at the

29   maximum radial distance from the axis 19 and in Fig. 9 at the minimum radial

1 distance from said axis 19. The rotational displacement is achieved by

2 rotating the ring pair 9/10 carrying the blade 33 around the axis 19.

3 Combinations of the radial and the rotational displacement of each blade

4 allow the creation of a great variety of peripheral shapes for the aperture 44.

5 The elliptical shape of the 39 has been chosen to give a relatively stiff

6 blade as well as a continuous and smooth outer perimeter of the body. Hereby

7 the bodies of the blades will not interfere with one another when they are

8 displaced relative to one another even though the axial spacing of the bodies

9 is small. So as to avoid such mutual interference between the bodies as well as

10 between the pairs of arms 30a,b-33a,b it is advantageous that the radial

11 displacement of the bodies take place in such a manner that practically no

12 flexing of the arms takes place during such displacement, i.e. that the distance

13 between the ends of the arms of each pair is constant during such radial

14 displacement and that no torsional forces are exerted on the arms during such

15 radial displacement.

16 In the currently preferred embodiment of the invention shown in Figs.

17 1-9, this is achieved as follows:

18 Each arm is provided with an angled end portion 45 having a guiding

19 pin 46 extending therethrough and projecting from both opposed surfaces of

20 the angled portion 45. The plane of each end portion 45 is substantially

21 parallel to the plane of the body 38 of the respective blade.

22 The rings of each pair of rings, for instance 15 and 16 in Fig. 6 or 9

23 and 10 in Fig. 8-9, are identical, and one lateral surface of each ring is

24 provided with a recessed circumferentially extending track 47 in the bottom of

25 an annular circumferentially extending recess 48 and an elongate radially

26 extending track 49 in the bottom of an annular circumferentially extending

27 recess 50 identical to the recess 48 and arranged diametrically opposite the

28 recess 48.

1   The two rings 15, 16 in Fig. 6 and the two rings 9, 10 in Figs 8 and 9

2   are arranged abutting each other with the lateral surfaces thereof provided

3   with the recesses 48 and 50 facing one another such that the recess 48 of the

4   ring 15 (ring 9) faces and overlies the recess 50 of the ring 16 (ring 10), and

5   the recess 50 of the ring 15 (ring 9) faces and overlies the recess 48 of the ring

6   16 (ring 10). Hereby annular channels 51 for receiving the angled end

7   portions 45 of the arms are formed when the rings of a pair 9/10, 11/12, 13/14

8   or 15/16 are arranged abutting each other.

9   One of the two projecting ends of each guiding pin 46 of each end

10   portion 45 is inserted in the circumferential track 47 of one ring of a pair of

11   rings while the other projecting end is inserted in the radial track 49 of the

12   other ring of said pair of rings.

13   The geometries of the tracks 47 and 49 are such that when one ring of a

14   pair of rings is rotated relative to the other ring of the pair, then the respective

15   body 38 of the blade carried by the pair of rings in question is displaced

16   radially such that the distance between the pins 46 of the two arms of the

17   respective blade remains constant and the arms are not subjected to any

18   torsional stresses.

19   In Figs. 8 and 9 the ring pair 9/10 is shown with the ring 9 abutting and

20   overlying the ring 10. In the illustration both rings are shown in full lines for

21   the sake of clarity and to illustrate the relative positions of the tracks 47 and

22   49 of both rings.

23   In Fig. 8 the ring 10 has been turned 10 degrees clockwise such that the

24   track 47 thereof shown at left in Fig. 8 is turned 10 degrees clockwise, while

25   the ring 9 has been turned 10 degrees counterclockwise so that the track 47

26   thereof shown at right in Fig. 8 is turned 10 degrees counterclockwise.

27   Consequently the track 49 of the ring 10 shown at right in Fig. 8 is turned 10

28   degrees clockwise while the track 49 of the ring 9 shown at left in Fig. 8 is

29   turned 10 degrees counterclockwise. The angles clockwise and

1 counterclockwise are given relative to an initial position where the body 38 is

2 at the halfway position between Fig.8 and Fig.9. The maximum periphery of

3 the light beam is shown by the circle 52.

4   In Fig. 9 the ring 10 has been turned 10 degrees counterclockwise such

5 that the track 47 thereof shown at left in Fig. 9 is turned 10 degrees

6 counterclockwise, while the ring 9 has been turned 10 degrees clockwise so

7 that the track 47 thereof shown at right in Fig. 9 is turned 10 degrees

8 clockwise. Consequently the track 49 of the ring 10 shown at right in Fig. 9 is

9 turned 10 degrees counterclockwise, while the track 49 of the ring 9 shown at

10 left in Fig. 9 is turned 10 degrees clockwise.

11   All intermediate positions between the two end positions shown in

12 Figs. 8 and 9 are achieved by rotating the rings 9 and 10 relative to one

13 another the corresponding amount of degrees between zero and twenty.

14   A multitude of different beam periphery shapes may be achieved by

15 displacing the blades 30-33 radially by rotating the two rings of the

16 corresponding ring pair relative to one another and by displacing the blades

17 circumferentially by rotating the two rings of a ring pair together.

18   In Fig. 7 one of infinitely many combinations of radial and

19 circumferential positions of the four blades 30-33 is shown, whereby a beam

20 44 with the shown eight sided polygonal peripheral shape is achieved.

21   So as to achieve a distance between the two pins 46 at the ends of the

22 two arms of each of the blades 30-33 that is the same for all radial

23 displacements of the body 38 thereof, and so as to provide that no torsion of

24 the arms takes place such that the body 38 is not subjected to any distorting

25 forces, the shapes of the tracks 47 and 49 are configured accordingly as

26 described in the following, with reference to Fig. 10 which illustrates the

27 construction and calculation of the said shapes of the tracks 47 and 49.

28   In Fig. 10 three pairs of mutually corresponding points on the curves

29 47 and 49 are constructed, the angles being exaggerated for the sake of clarity.

1   The construction of the curves is carried out according to the

2   following:

3   A1 is constant and equal to half the distance between the two pins 48

4   of a blade.

5   C2 = A1

6   Angle1 = Angle2

7   Angle1 + Angle2 = Angle3

8   Both triangles are right-angled triangles

9   Angle 1 is the angle at which ring 1 is set, and Angle 2 is the angle at

10   which ring 2 is set

11   By rotating ring 1 relative to ring 2, Angle 3 is obtained. A center line

12   is constructed from the center of the rings and horizontally to the left such that

13   Angle 1 = Angle 2.

14   Angle 1 and Angle 2 are used to construct two triangles.

15   A line is drawn along the center line, the line having a length equal to

16   half the length between the two pins 46 of a blade.

17   This line forms the hypotenuse C2 as well as the triangle side A1 so

18   that the other triangle side B1 can be constructed by drawing a line from the

19   right angle downwards and C1 away from the center until the two lines

20   intersect at a point. This point is on the curve to be constucted for configuring

21   track 47.

22   Equation 1.1: $B1 = SIN(Angle\ 1) \times A1$

23   Equation 1.2: $C1 = A1/COS(Angle\ 1)$

24

25   C1 is now a radius which together with Angle 3 may used to construct

26   the track by means of the equations 1.3:

27        $Xtrack47 = COS(Angle\ 3) \times C1$

28        $Ytrack47 = SIN(Angle\ 3) \times C1$

29   Or the equation 1.2 may be inserted in the equation 1.3:

1   Xtrack47 = COS(Angle 3) x (A1/COS(Angle 1))

2   Ytrack47 = SIN(Angle 3) x (A1/COS(Angle 1))

3   The X and Y axes are as indicated in Fig. 10 for each point

4 constructed.

5   The track 49 in one ring extends in the radial direction to take up the

6 radial displacement of the corresponding end of the pin 46 arising from the

7 geometry of the track 47 in the other ring.

8   As it is the intersection point or triangle apex B1/C1 that alters its

9 position relative to the center of the rings, the shape of the track 47 is given

10 by:

11   X track49 = A1/COS(Angle 1)

12   Ytrack49 = 0

13   such that the fixed distance is maintained between the ends of the pins

14 46 in corresponding points of tracks 47 and 49.

15   Those skilled in the art will readily appreciate that it is possible to

16 achieve displacement of beam shaping blades radially and circumferentially

17 by means of rotating rings in many other ways.

18   Referring now to Fig. 11, an alternative way of arranging the beam

19 shaping blades is shown schematically. Two adjustment rings 56, 57 similar to

20 the adjustment rings 9,10 of Figs. 8 and 9 are arranged abutting each other

21 with a beam shaping blade 60 arranged therebetween and attached to the rings

22 by means of two guiding pins 61 and 62. The pin 61 is received in a recess in

23 the lateral surface of the ring 57 facing the ring 56, the recess having a shape

24 that only allows rotation of the pin 61 therein. The pin 62 is received in a

25 linear track 63 recessed into the lateral surface of the ring 56 facing the ring

26 57. The pin 62 may slide in the track 63.

27   The situation wherein the blade 60 maximally obstructs the beam of

28 light 52 is shown in full lines while the situation wherein the blade 60 does

29 not obstruct the beam 52 is shown in dotted lines. The fully obstructing

1 position of the blade 60 is amended to the non-obstructing position thereof by

2 rotating the rings 56 and 57 relative to one another, for instance as shown by

3 rotating the ring 56 counterclockwise and maintaining the ring 57 in the same

4 position. Hereby the pin 62 will be forced to slide in the track 63 while the pin

5 61 merely rotates such that the blade rotates around the pin 61. In the shown

6 example a rotation of the ring 56 counterclockwise 12 degrees will result in a

7 rotation of 22 degrees of the blade 60.

8 This arrangement of the beam shaping blades requires relatively stiff

9 blades and/or relatively large axial spacing between the individual blades so

10 that the blades will not interfere with or engage one another when being

11 rotated.

12 Referring now to Figs. 2, 3, 12 and 13, the mechanism for displacing

13 the focusing lens 22 and the zoom lens 23 along the longitudinal axis 19 is

14 shown in partly exploded form. A holder 64 for the zoom lens 23 and a

15 holder 65 for the focusing lens 22 are slidingly arranged in tracks 66 and 67,

16 respectively, in track rails so that the holders 64 and 65 may be displaced to

17 and fro parallel to the longitudinal axis 19.

18 A bracket 68 is connected to each of the holders 64 and 65, only the

19 bracket 68 for the holder 65 being visible. The brackets are each connected to

20 a respective toothed belt 69 and 70 corresponding to the holders 65 and 64,

21 respectively. The toothed belts are mounted on pulleys 71 and 72 rotatably

22 mounted on the track rails 66, 67.

23 Each of the adjustment rings 17 and 18 (partly cut away for clarity in

24 Fig. 12) are provided with lateral toothed portions 73 and 74, respectively, for

25 engaging the teeth of the toothed belts 69 and 70, respectively, so that rotation

26 of the ring 17 to and fro will cause displacement of the toothed belt 69 to and

27 fro, and rotation to and fro of the ring 18 will cause displacement to and fro of

28 the toothed belt 70. Hereby, the lens holders 64 and 65 may be displaced to

29 and fro along the tracks 66 and 67 by rotation to and fro of the rings 18 and

1   17, respectively.

2   Hereby, a simple, precise and relatively silent displacement mechanism

3   is achieved for adjusting the position of the lenses along the longitudinal axis.

4   When the lighting fixture 1 is oriented with the áxis 19 thereof steeply

5   inclined, i.e. pointing upwards or downwards steeply, the weight of the lenses,

6   particularly the zoom lens 23, will tend to force the lens up or down from the

7   desired and adjusted position, especially if vibration of the fixture takes place.

8   This tendency can be curtailed or eliminated by introducing an inertia or

9   braking in the displacement mechanism.

10   However, if the inertia is present constantly, for instance a constant

11   brake force applied to the toothed belts, then displacement of the lens will

12   require additional tangential force applied to the rims of the rings 17 and 18.

13   Naturally, this is undesirable both for manual operation, requiring greater

14   exertion of force by the operator's fingers, and for motorized operation,

15   requiring a more powerful motor with attendant increases in costs and

16   possibly noise.

17   The displacement mechanism according to the invention is provided

18   with a braking function that only is effective when displacement of the lens is

19   not taking place, i.e. the braking function is only in force when the rings 17 or

20   18 are not being rotated. The principles of the selective braking mechanism

21   according to the invention and described in the following are of course also

22   applicable in other applications where a displacement of an object with

23   subsequent braking of the object in the displaced position is desirable.

24   The selective braking mechanism (Figs. 12-13) according to the

25   invention comprises the pulley 71, a locking wheel 90, a friction washer 91, a

26   friction spring 92, a locking washer 93 and a locking sled 94. The spring 92

27   presses the locking wheel 90 and the friction washer 91 against the pulley 71

28   so as to create a suitable friction between the locking wheel 90 and the pulley

29   71. The locking sled 94 is arranged between the two parallel lengths of the

1 toothed belt and for displacement to and fro in the plane of said toothed belt

2 70, perpendicularly to said two parallel lengths. The locking sled is provided

3 with locking teeth 94a and 94b for locking engagement with teeth at the rim

4 of locking wheel 90 in a ratchet type action. If the locking sled 94 is in a

5 central position, i.e. not displaced toward any of the two parallel lengths of the

6 belt 70, then the locking teeth 94a and 94b will not engage the teeth of the

7 locking wheel 90 so no friction brake is applied to the belt 70.

8 The dimension of the locking sled 94 perpendicular to the parallel

9 lengths of the belt 70 is slightly longer than the distance between the common

10 tangents of the pulleys 71 and 72 such that in the central position of the

11 locking sled 94, the locking sled will press against the parallel lengths of the

12 belt 70.

13 If tension is applied to one of the parallel lengths of the toothed belt 70

14 because of the weight of the lens, said length will be tightened and the parallel

15 length will be loosened whereby the locking sled 94 will be displaced from

16 the central position to a lateral position where the respective one of the

17 locking teeth 94a and 94b will engage the ratchet teeth of the locking wheel

18 90, thereby applying frictional braking forces to the pulley 71 through the

19 friction washer 91.

20 However, if tension in one of the parallel lengths of the belt 70 is

21 caused by rotation of the ring 18 for axial displacement of the holder 64, then

22 the displacement of the locking sled 94 from the central position thereof will

23 not cause engagement of one of the locking teeth 94a or 94b with the ratchet

24 teeth of the locking wheel 90 as the ratchet effect will cause the respective

25 locking tooth to "ratchet" over the ratchet teeth.

26 Hereby, a selective braking mechanism is achieved whereby the brake

27 effect is operative, when the weight of the lens tries to rotate the respective

28 adjustment rings, but the brake effect is inoperative when rotation of the

29 respective ring is carried out to displace the lens axially.

1   It will be apparent to those skilled in the art that the principles of the

2   above selective braking mechanism may be applied in all applications where a

3   braking effect is required in one direction of force application and is not

4   required in the opposite direction of force application.

5   The arrangement of the gobo or pattern 29 in the ring 8 and the iris 28

6   in the ring 7 need not be described herein as it will be apparent to those

7   skilled in the art that this can be done in many ways well known in the art.

8   For remote control of the adjustment rings it will also be readily

9   apparent to those skilled in the art that an electrical motor with a pinion for

10   each ring may be arranged such that the teeth of the pinion mesh with the

11   teeth on the rim of the respective ring. The motors may for instance be firmly

12   attached to the frame 6 or be spring biased so that any irregularities in the

13   mounting of the rings and thereby the teethed rims may be taken up. Magnetic

14   markers may be attached to the rings such that a sensing means may sense the

15   marker and thereby precisely identify the position of the respective ring as a

16   basis for the subsequent rotation thereof to a new setting of the respective

17   beam influencing means.

18

19